

Response

Applicant: DuWayne C. Radke et al.

Serial No.: 09/904,124

Filed: July 12, 2001

Docket No.: M120.199.101 (56908US002)

Title: PASS-THROUGH FIRESTOP DEVICE

IN THE CLAIMS

With this Response, the claims have not been amended and remain as follows:

1. (Previously Presented) A firestop device for providing a passage through a partition in a structure, comprising:
 - (a) a housing; and
 - (b) firestop material arranged within said housing;said housing including at least one frangible connection defining a removable band.
2. (Previously Presented) A firestop device as defined in claim 1, wherein said band includes a pull tab, said pull tab providing grasping means for allowing a user to remove said band from said housing at said frangible connection.
3. (Previously Presented) A firestop device as defined in claim 1, wherein said housing comprises a base portion and a riser portion, said base portion including a recess for receiving said firestop material, and said riser portion including said frangible connection.
4. (Previously Presented) A firestop device as defined in claim 3, wherein said base portion includes a sidewall portion extending from a first open end to toward said riser portion, and a shoulder portion extending inwardly from said sidewall portion to said riser portion, said sidewall portion and said shoulder portion defining said recess for receiving said firestop material.
5. (Previously Presented) A firestop device as defined in claim 4, wherein said sidewall and said shoulder portions include inner surfaces having ribs.

Response

Applicant: DuWayne C. Radke et al.

Serial No.: 09/904,124

Filed: July 12, 2001

Docket No.: M120.199.101 (56908US002)

Title: PASS-THROUGH FIRESTOP DEVICE

6. (Previously Presented) A firestop device as defined in claim 5, wherein said housing has first and second opposed open ends and a hollow chamber having a longitudinal axis extending from said first open end to said second open end.

7. (Previously Presented) A firestop device as defined in claim 6, wherein said first open end is provided in said base portion and said second open end is provided in said riser portion, said firestop material being provided in spaced relation along said sidewall portion inner surface from said first open end to said shoulder portion.

8. – 9. (Cancelled)

10. (Previously Presented) A firestop device as defined in claim 3, wherein said riser portion includes a plurality of equally segmented transverse bands each including a manually engageable pull tab.

11. (Previously Presented) A firestop device as defined in claim 10, wherein each said pull tab includes indicia indicating the length of the device at each band corresponding to the thickness of the partition.

12. (Previously Presented) A firestop device as defined in claim 11, further comprising a cap attached to said riser portion thereby to cover said second open end.

13. (Previously Presented) A firestop device as defined in claim 12, wherein said cap contains snap connectors that snap onto said riser portion, thereby to attach said cap to said riser portion.

Response

Applicant: DuWayne C. Radke et al.

Serial No.: 09/904,124

Filed: July 12, 2001

Docket No.: M120.199.101 (56908US002)

Title: PASS-THROUGH FIRESTOP DEVICE

14. (Previously Presented) A firestop device as defined in claim 11, further comprising an extension member adapted to connect with said riser portion adjacent said open second end.

15. (Previously Presented) A firestop device as defined in claim 3, further comprising a retaining ring arranged within said base portion first open end adjacent said firestop material.

16. (Previously Presented) A firestop device as defined in claim 15, wherein said retaining ring is coded to indicate the quantity of firestop material provided in the device depending on the application of the device.

17. (Previously Presented) A firestop device as defined in claim 11, further comprising an adapter connected with said base portion for coupling said device to a contoured surface.

18. (Previously Presented) A firestop device for providing a passage through a partition in a structure comprising a housing having first and second opposed open ends and a hollow chamber having a longitudinal axis extending from said first open end to said second open end, said housing including a cylindrical base portion having a diameter and a cylindrical riser portion having a diameter smaller than said base diameter, said base portion including an annular sidewall portion extending from said first open end toward said riser portion and a shoulder portion extending radially inwardly from said sidewall portion to said riser portion, said sidewall portion and said shoulder portion defining an annular recess for receiving firestop material, said sidewall and said shoulder portions including inner surfaces having inwardly extending ribs, said riser portion including a plurality of longitudinally arranged frangibly connected circumferential bands having equal axial lengths, each band including a radially

Response

Applicant: DuWayne C. Radke et al.

Serial No.: 09/904,124

Filed: July 12, 2001

Docket No.: M120.199.101 (56908US002)

Title: PASS-THROUGH FIRESTOP DEVICE

outwardly extending pull tab that can be used to manually remove a band from said riser portion along a frangible connection, thereby to reduce the height of the device in accordance with the thickness of the partition into which the device is installed.

19. (Previously Presented) A firestop device as defined in claim 2, wherein said pull tab extends radially outwardly from said band.

20. (Previously Amended) A firestop device as defined in claim 5, wherein said sidewall ribs extend longitudinally from said first open end along said shoulder portion along said inner surface, thereby defining a gap between said firestop material and said sidewall inner surface.

21. (Cancelled)

22. (Previously Presented) The firestop device of claim 1, wherein said housing further includes a pull tab connected to said releasable band, said pull tab extending from an outer surface of said releasable band.

23. (Previously Presented) A firestop device for providing a passage through a partition in a structure, comprising:

(a) a housing including a cylindrical base portion and a cylindrical riser portion, said riser portion having a smaller diameter than said base portion, wherein said riser portion includes:

(1) a frangible connection defining a removable band circumscribing said riser portion, and

Response

Applicant: DuWayne C. Radke et al.

Serial No.: 09/904,124

Filed: July 12, 2001

Docket No.: M120.199.101 (56908US002)

Title: PASS-THROUGH FIRESTOP DEVICE

- (2) a pull tab connected to, and extending radially outwardly from
said band; and
- (b) firestop material arranged within said base portion.